

Rotating Log Grab



The Ultimate Solution for Efficient Timber & Material Handling

Hamilton Diggers Rotating Log Grabs are purpose-built for the demands of New Zealand operators - engineered with precision to ensure exceptional productivity, safety, and service life. Designed to suit 5-8 tonne excavators, this grab is ideal for working with logs, posts, scrap timber, demolition debris, and storm-felled vegetation. Whether you're operating on a forestry block, clearing fence lines, or handling material in tight access spaces, our log grab delivers the strength and performance needed to keep operations moving efficiently.

Premium Engineering for Maximum Reliability

Experience genuine 360° continuous rotation, powered by a high-grade M&S rotator motor, offering smooth and controlled positioning at every angle. A dependable brake system ensures firm holding power while gripping, lifting, or sorting material — even on uneven terrain.

Built to last, the grab features:

- Heavy-duty rotator bearings and ring gears for superior strength
- High-grade steel construction for impact resistance
- Optimised pivot geometry for stronger, more stable clamping force
- Replaceable wear components designed for long service life

Operator-Focused Design

Five-hose configuration (2 × grab function + 2 × rotation + 1 × case drain) delivers smooth flow management and precise hydraulic control.

Fully adjustable pivot joints allow tailored fit and simplified servicing, helping reduce downtime and maintenance costs. With excellent material visibility, the operator can manoeuvre confidently — improving job-site safety and efficiency.

Backed by a 1-year manufacturers warranty, giving you complete trust in the integrity of your Log Grab. **One attachment — endless capability.**



ROTATING LOG GRAB	HD02	HD04	HD06	HD08	HD10
To Suit Excavator	4-6 Tonne	7-11 Tonne	12-16 Tonne	17-23 Tonne	24-30 Tonne
Max Jaw Opening	1300 mm	1400 mm	1800 mm	2300 mm	2500 mm
Oil Pressure	110-140 Kg/cm ²	120-160 Kg/cm ²	150-170 Kg/cm ²	160-180 Kg/cm ²	160-180 Kg/cm ²
Working Oil Flow	30-55 L/min	30-55 L/min	40-70 L/min	40-70 L/min	40-70 L/min
Max Cylinder Force	4 Tonne x 2	4.5 Tonne x 2	8.0 Tonne x 2	9.7 Tonne x 2	12 Tonne x 2
Weight	320 Kg	390 Kg	740 Kg	1380 Kg	1700 Kg



6A Sloper Avenue, Frankton,
Hamilton 3204



hamiltondiggers@gmail.com
www.carterexcavators.co.nz



021 1154 722