

# Flail Mower



Our versatile flail mowers are designed to fit excavators ranging from 1.7 to 14 tonnes, making them a powerful and reliable addition to your equipment lineup.

This innovative hammer-type flail mower excels in scrub clearing and verge mowing, effortlessly handling up to 90mm of green gorse and up to 40mm of dry woody material with ease.

## Features:

- Includes hoses and 1/2-inch couplers
- 90 degree mounting base (N/S and E/W positioning)
- Dual belt drive (HD800), Triple belt drive (HD1000 & HD1200)
- External relief valves
- Swing mount and hoses included

For added convenience, a hitch can be supplied to suit your specific excavator upon request. The 90-degree mounting base can be easily adjusted from side-ways to a length-ways configuration, allowing you to adapt to different job requirements effortlessly.

We offer the flexibility of both flat and fork-Y cast hammers. Replacement blades and other spare parts are available in stock for when replacement is required.

Every Hamilton Diggers flail mower is backed by a 2-year warranty, giving you confidence in your investment and the reliability you can count on for all your mowing needs.



FLAIL MOWER	HD800	HD1000	HD1200
Cutting Width	800mm	1000mm	1200mm
To Suit Excavator	1.7-3.6 Tonne	3.5-10 Tonne	8-14 Tonne
Cutting Height	20-50 mm	20-50 mm	20-50 mm
No. of Belts	2	3	3
Weight	115 Kg	250 Kg	280 Kg
Motor Speed	2000-2400 r/min	2000-2400 r/min	2000-2400 r/min
Working Pressure	18 MPa	18 MPa	18 MPa
Excavator Flow	22ml/r motor: 30-40 L/min	29ml/r motor: 35-50 L/min 40ml/r motor: 50-70 L/min	40ml/r motor: 50-70 L/min 63ml/r motor: 80-120 L/min



6A Sloper Avenue, Frankton,  
Hamilton 3204



hamiltondiggers@gmail.com  
www.carterexcavators.co.nz



021 1154 722